



ZAC Grenoble Air Parc Est
Avenue Louis Blériot
FR-38590 ST ETIENNE DE ST GEOIRS
Tél. : +33.(0)4.76.07.37.37
Fax : +33.(0)4.76.91.04.97
info@signs-europa.fr
www.signs-europa.fr

FICHE TECHNIQUE

Adhésif Microperforé 160 μ - Réf. NT88

Laizes disponibles	0.98 m, 1.37 m & 1.52 m	Classe	Extérieur
Longueur	50 m	Mandrin	3'

Description :	Vinyle adhésif microperforé pour impression numérique solvant et écosolvant
----------------------	---

Produit	Valeurs ou Conclusions	
Film PVC	Composition	Finition brillante, Film PVC noir
	Epaisseur	160 μ (0.16mm)
	Poids	130g/m ²
	Retrait	<1.9%
	Taille des trous	1,45 mm
	Transparence	52%
	Durabilité	1 an en conditions normales, sans pollution ou exposition aux UV excessive
Adhésif	Type d'adhésif	Adhésif acrylique blanc semi-enlevable
	Température	-20°C ~ 70°C
	Adhérence	Test sur acier inoxydable, 300N/m.
	Adhérence finale	Test sur acier inoxydable, 450N/m.
Support papier	Type	Papier renforcé, une face silicone Kraft paper with one-side silicone backing
	Couleur	Blanc
	Poids	160g/ m ²
	Epaisseur	185 μ (0.185mm)
Stockage	1 an – Température de stockage à 22 °C – Humidité r elative 50~55%	
Durabilité	Jusqu'à 1 an (appliqué verticalement)	
Applications	Décors de vitrine et fenêtre	

NOTE :

Données non contractuelles, sous réserve de modification sans préavis. Il appartient à l'utilisateur de s'assurer de la compatibilité du produit avec son utilisation. Il est de la responsabilité du producteur de remplacer tout produit qui s'avèrerait défectueux suite à un vice de fabrication.



ZAC Grenoble Air Parc Est
Avenue Louis Blériot
FR-38590 ST ETIENNE DE ST GEOIRS
Tél. : +33.(0)4.76.07.37.37
Fax : +33.(0)4.76.91.04.97
info@signs-europa.fr
www.signs-europa.fr

DATA SHEET

One Way Vision 160 μ - Ref. NT88

Available Widths	0.98 m, 1.37 m & 1.52 m	Class	Outdoor
Length	50 m	Core	3'

Description :	One Way Vision microperforated vinyl for solvent and ecosolvent ink
----------------------	---

Item	Value or Conclusions	
PVC film	Composition	Glossy finish, Black PVC film
	Thickness	160 μ (0.16mm)
	Weight	130g/m ²
	Shrinking	< 1.9%
	Transparency	52%
	Durability	1year (in normal situations, such as without pollution and direct sunshine irradiation)
Adhesive	Adhesive Type	Half-removable, White acrylic adhesive
	Temperature Range	- 20°C ~ 70°C
	Tack	Test while adhering to stainless steel, 300N/m.
	Final Tack	Test while adhering to stainless steel, 450N/m.
Release Paper	Type	Kraft paper with one-side silicone backing
	Color	White
	Weight	160g/ m ²
	Thickness	185 μ (0.185mm)
Storage Period	1year (Storage temperature of 22 \square , relative humidity of 50 ~ 55%)	
Durability	1year (vertically hung)	
Applications	Windows Graphics, Glass backdrops.	

NOTE :

The data are provided for information only, all details are subject to change without notice. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. The user of the product assumes the obligation to determine the suitability of the product for each particular application and assumes all risks and liability related to such use. It is producer's responsibility to the replacement of any product proven to be defective at the time of application due to a manufacturing anomaly.